

## 19" DYNAMIC Basic Server Cabinets

Width: 600 mm.  
Depth: 1000 mm.

Width=600mm

Depth=1000mm

Standard Heights:

3 different U heights: 26U, 36U, 42U

Standards, and Compliances:



**ISO 9001:2008**  
Quality Management System

EN 61587 -1:2012  
Mechanical Structures for  
Electronic Equipment

IEC 297-1, 19" mounting  
IEC 297-2 Overall cabinet dimensions



**CE conform to**  
EN 60950-1:2006  
Information Technology  
Equipment – Safety – Part-1-  
General Requirement



**UL listed to**  
UL 2416, Outline of Investigation for  
Audio/Video, Information and  
Communication Technology Equipment  
Cabinet, Enclosure and Rack Systems;  
UL 60950-1 and CSA C22.2 NO.  
60950-1-07, Information Technology  
Equipment Safety Part 1: General  
Requirements




**Environment Friendly;**  
\* **ISO 14001** Environmental  
Management System  
\* RoHS compliancy  
\* %100 Recyclable Material

Load Capacity: 600 kgs.



DYNAMIC series Networking Enclosures, with  
19" w:600mm and d:1000mm physical sizes, with  
max internal usable depth and 3 different heights.

Standard Colors:




RAL 9005 Black




RAL 7035 Light Grey




DRAWINGS




BOTTOM VIEW




FRONT VIEW



SIDE VIEW




REAR VIEW




TOP VIEW


DRAWINGS




ISOMETRIC VIEW




EXPLODED VIEW



FRONT AND REAR DOOR OPENING ANGLE



MAX/STD/MIN EQUIPMENT MOUNTING DISTANCE



DIMENSIONS IN WIDTH AND HEIGHT

DYNAMIC Basic Series Free Standing Server 19" Cabinets W=600mm D=1000mm with perforated doors

ROOT Product Number ***	Product Description	Size W X D X H mm	HU size (U)	HU in mm	*H mm, overall without feet and/or castor	Width Overall mm	Width Rail to Rail	Depth Overall mm	**Depth Shipping Conf. Rail to Rail mm	QTY IN PACKAGE	ASSEMBLED PACKAGE DIMENSIONS W X D X H	Standard NET Weight of product kgs	Gross Weight of Products kgs
LN-DS26U6010-CC	26U 19" Free Standing Cabinet W=600mm D=1000mm Perforated % 63 front and rear doors	600x1000x1300	26U	1155	1300	600	19"	1000	770	1	680x1080x1440	59	69
LN-DS36U6010-CC	36U 19" Free Standing Cabinet W=600mm D=1000mm Perforated % 63 front and rear doors	600x1000x1744	36U	1599	1744	600	19"	1000	770	1	680x1080x1884	88	97
LN-DS42U6010-CC	42U 19" Free Standing Cabinet W=600mm D=1000mm Perforated % 63 front and rear doors	600x1000x2010	42U	1867	2010	600	19"	1000	770	1	680x1080x2150	94	105

\* Please add 30mm to H mm once used with Leveling Feet, add 80mm to H mm once used with castor set. \*\* See min and max Adjustable depth variations on drawings.  
 \*\*\* CC= LG for Light Grey RAL 7035 & BL for Black RAL 9005 for customers to define while ordering.  
 \*\*\*\* Unless defined delivery is in Flat Pack, Please add A notation to The Part number for assembled delivery ie. LN-DS26U6010-CC-A  
 \*\*\*\*\* The Logistical information provided in above chart is based on assembled product since packing details of flat-pack is changing based on transport vehicle and the delivery location. Please consider delivery notes, packing lists and recent data provided with the logistics services of Lande.

## 19" DYNAMIC Basic Server Cabinets / W:800mm- D:1000mm

W=800mm D=1000mm DYNAMIC Basic Series Server Cabinets.

DYNAMIC Basic series Server Cabinets, provide maximum optimization resulted to an optimum performance in between quality and added value.

While product gives maximum performance on servering and storage infrastructure, in parallel provides a very valuable economy compared to its quality which is based on high technologic fully automated industry.

The 800 series is available in 42U, with 1000mm depth.

Each cabinet is supplied as standard with a %63 perforated single piece monoblock front and rear door, steel rear panel and lift off steel side panels, all of which are lockable.

DYNAMIC Basic series Server Cabinets have a professional technical but aesthetic look with decorative %63 perforated honey comb pattern. The product range attracts the attention with the mostly environmentally fit and selected color of RAL 9005 Black, and RAL 7035 Light Grey, with fine wrinkle soft touch paint.

Completely standard and stocked product portfolio, being delivered as un-assembled in flat pack, as shipping configuration the adjustable feet group is included.

DYNAMIC Basic series server product range with optimal panel mounting size, and a variety range of accesories enclose the whole expectation of users.

W800xD1000mm



## CONSTRUCTION DETAILS:

Main Profile- Framework- Top/Bottom Cases:

Multi Folded Automated Bending technology applied corner profile system, provides a heavy duty structure results to high load capacity of: 600 kgs.

Monoblock multi folded top and bottom cases, tightly fixed to the framework with fixing hardware, fully modular system generated.

Top case has a ready Forced Ventilation (Fan Module) integration housing.

Bottom case integrated with Wide cable entry point provides maximum versatility. The knock out panel style cable entry point at bottom with  $w=350\text{mm} \times d=250\text{mm}$  allows large cabling infrastructure applications.

Additionally both on sides of top and bottom case, there is PVC Dummy plate covered cable entries  $70 \times 316\text{mm}$  are available. Once cables to be inserted these dummy plates to be removed. In case needed these dummy Plates could be replaced with brushed cable entry plates on site.



## CONSTRUCTION DETAILS:

Access to enclosure:

Front door and rear doors are %63 perforated single piece monoblock front single point locking handled lock.

Colors are RAL 7035 Light Grey Cabinet and for RAL 9005 Black.

Front door opening direction is set right to left, but reversible to left to right at site with removing the hinge system. Hinge System is spring loaded easy operating version, which allows you to remove the whole front door from cabinet in seconds.

Side Panels are lockable and removable with barrel style lock, Multifolded bending technology with 8 fold bending provides the rigidity. Easy mechanical locking of panel to main frame with snap capture sytem allows easy attachment of panels and easy removal in seconds while installation in process.

Rear Panels are lockable and removable with barrel style lock, Multifolded bending technology with 8 fold bending provides the rigidity. For best optimized cost conduction to customers, the rear panel designed and created with same mechanical concept and sizes of the side panels.



## 19" DYNAMIC Basic Server Cabinets / W:800mm - D:1000mm

### CONSTRUCTION DETAILS:

19" rails of DYNAMIC Basic Series Server cabinets are with automated silk-screen U numbering, depends on size 1U to 42U, same from top to bottom or bottom to top results to same U height selection. No matter from where you have started counting.

19" rails are 4 fold bending surfaces, 1,5mm thickness provides the high load capacities. The 19" rails are made of steel with 8-12 micron zinc plating for corrosion resistance. 19" rails are adjustable in depth. For easy adjustment purpose, no need to detach the screws, just ease the screws and slide them in the channels on the top/bottom chasis bends.

Side Horizontal Support Bar in depth; integrated with 1 set (left/right), 1,5mm thickness Z type made of Steel + 8-12 micron zinc plated side horizontal support bar

All design features provide 4 way access to your enclosure and equipments, easy to reach to enclosure and equipments for all infrastructure installations and maintenance needs.



## 19" DYNAMIC Basic Free Standing Cabinets

Width: 800 mm.  
Depth: 1000 mm.

Width=800mm  
Depth=1000mm

Load Capacity: 600 kgs.

Standard Heights:

42U height:

Standards, and Compliances:



**ISO 9001:2008**  
Quality Management System

EN 61587 -1:2012  
Mechanical Structures for  
Electronic Equipment

IEC 297-1, 19" mounting  
IEC 297-2 Overall cabinet dimensions



**CE conform to**  
EN 60950-1:2006  
Information Technology  
Equipment – Safety – Part-1-  
General Requirement



**UL listed to**  
UL 2416, Outline of Investigation for  
Audio/Video, Information and  
Communication Technology Equipment  
Cabinet, Enclosure and Rack Systems;  
UL 60950-1 and CSA C22.2 NO.  
60950-1-07, Information Technology  
Equipment Safety Part 1: General  
Requirements



**Environment Friendly;**  
\* **ISO 14001** Environmental  
Management System  
\* RoHS compliancy  
\* %100 Recyclable Material



DYNAMIC series Networking Enclosures, with 19" w:800mm and d:1000mm physical sizes, with max internal usable depth, and 2 different heights.

All W=800mm model cabinets are constructionally proper for the Vertical Cable Management panels.

Standard Colors:




RAL 9005 Black




RAL 7035 Light Grey




DRAWINGS




BOTTOM VIEW




FRONT VIEW



SIDE VIEW




REAR VIEW




TOP VIEW


DRAWINGS




ISOMETRIC VIEW




EXPLODED VIEW



FRONT AND REAR  
DOOR  
OPENING ANGLE



MAX/STD/MIN  
EQUIPMENT MOUNTING  
DISTANCE



DIMENSIONS  
IN  
WIDTH AND HEIGHT

DYNAMIC Basic Series Free Standing 19" Cabinets W=800mm D=1000mm with perforated doors

ROOT Product Number ***	Product Description	Size WxDxH mm	HU size (U)	HU in mm	*H mm, overall without feet and/or castor	Width Overall mm	Width Rail to Rail mm	Depth Overall mm	**Depth Shipping Conf. Rail to Rail mm	QTY IN PACKAGE	ASSEMBLED PACKAGE DIMENSIONS WxDxH	Standard NET Weight of product kgs	Gross Weight of Products kgs
LN-DS42U8010-CC	42U 19" Free Standing Cabinet W=800mm D=1000mm Perforated % 63 front and rear doors	800x1000x2010	42U	1867	2010	800	19"	800	770	1	880x1080x2150	108	122

\* Please add 30mm to H mm once used with Leveling Feet, add 80mm to H mm once used with castor set. \*\* See min and max Adjustable depth variations on drawings.

\*\*\* CC= LG for Light Grey RAL 7035 & BL for Black RAL 9005 for customers to define while ordering.

\*\*\*\* Unless defined delivery is in Flat Pack, Please add A notation to The Part number for assembled delivery ie. LN-DS42U8010-CC-A

\*\*\*\*\* The Logistical information provided in above chart is based on assembled product since packing details of flat-pack is changing based on transport vehicle and the delivery location. Please consider delivery notes, packing lists and recent data provided with the logistics services of Lande.

# 19" DYNAMIC Basic Cabinets Flat Pack Delivery

## WHY FLAT PACK; WHAT MAKES SENSE in DYNAMIC BASIC!

Delivery of Dynamic Basic, configured as Flat Pack for reducing cost of logistics, comparatively 3 times higher qty can be stacked in transport vehicles which allows 3 times less logistical cost.

Customer friendly assembly, fully modular construction, zero risk of error design for customer assembly ( all potential assembly mistakes are avoided), less operation and labour cost while assembly operation to be performed.

Allowing better cost scheme in projects, since the infrastructure installer or customer might operate the assembly operation at site. Thus narrow doors, unavailability of goods-hoist and staircases are no more a problem.

No special assembly tool required.

Re-used Packing Material after assembly incase a second step delivery to be operated.

For customers who are performing the assembly in its own stocking locations, or full palletized delivery to the project site, OPTION A, Flat Packing Delivery with just cardboard protection and wooden shelving in between the boxes on palette offered. In this concept each Dynamic Basic cabinet consist of 2 pack/palette Pack A, all Vertical Parts, Panels, Profiles Pack B, Top and Bottom Cases.

For customers which is delivering the product, piece by piece to its distribution Network, without assembling the product before delivery, OPTION B, Flat Packing Delivery with cardboard protection and overall wooden crate packing is offered.

OPTION A PACKING- Showing PACK and PACK B



OPTION A PACKING - BEFORE HIGH STACK



OPTION A PACKING- AFTER HIGH STACK



\*\*\* In option-A Stacking- up to 16 sets of cabinets  
Can be palletized due to distance of delivery and available height inside transport vehicle ( truck/container)

OPTION B PACKING



\*\*\* In option B Stacking- up to 12 sets of cabinets  
Can be palletized due to distance of delivery and available height inside transport vehicle ( truck/container)

# 19" DYNAMIC Basic Free Standing and DYNAMIC Basic Server Cabinets Frequent Used Accessory Selection Chart



Frequent Used Accessories DYNAMIC Basic Series Free Standing Cabinets Sizes w:width mm d:depth mm					
	w:600xd:600	w:600xd:800	w:600xd:1000	w:800xd:800	w:800xd:1000
Fixed Shelves compatible with only Lande Cabinet	LN-RAF-SBT-D600-CC	LN-RAF-SBT-D800-CC	LN-RAF-SBT-D100-CC	LN-RAF-SBT-D800-CC	LN-RAF-SBT-D100-CC
Fixed Shelves Universal Mutivendor	LN-RAF-SBT-D600-CC-UNV	LN-RAF-SBT-D800-CC-UNV	LN-RAF-SBT-D100-CC-UNV	LN-RAF-SBT-D800-CC-UNV	LN-RAF-SBT-D100-CC-UNV
Heavy Duty Fixed Shelves	-	-	LN-RAF-SBA-D100-CC	-	LN-RAF-SBA-D100-CC

\*\*CC is color code: please insert BL for Black and LG for Light Grey on the part numbers while creating order



Frequent Used Accessories DYNAMIC Basic Series Free Standing Cabinets Sizes w:width mm d:depth mm					
	w:600xd:600	w:600xd:800	w:600xd:1000	w:800xd:800	w:800xd:1000
Sliding Shelves	LN-RAF-HRK-D600-CC	LN-RAF-HRK-D800-CC	-	LN-RAF-HRK-D800-CC	-
Heavy Duty Sliding Shelves	-	-	LN-RAF-HRA-D100-CC	-	LN-RAF-HRA-D100-CC

\*\*CC is color code: please insert BL for Black and LG for Light Grey on the part numbers while creating order



Frequent Used Accessories DYNAMIC Basic Series Free Standing Cabinets Sizes w:width mm d:depth mm					
	w:600xd:600	w:600xd:800	w:600xd:1000	w:800xd:800	w:800xd:1000
2 fan Units on/off switched	LN-FAN-ONF-2FFS-CC	LN-FAN-ONF-2FFS-CC	LN-FAN-ONF-2FFS-CC	LN-FAN-ONF-2FFS-CC	LN-FAN-ONF-2FFS-CC
2 fan Units with Thermostatic control Unit	LN-FAN-THM-2FFS-CC	LN-FAN-THM-2FFS-CC	LN-FAN-THM-2FFS-CC	LN-FAN-THM-2FFS-CC	LN-FAN-THM-2FFS-CC
4 fan Units on/off switched	LN-FAN-ONF-4FFS-CC	LN-FAN-ONF-4FFS-CC	LN-FAN-ONF-4FFS-CC	LN-FAN-ONF-4FFS-CC	LN-FAN-ONF-4FFS-CC
4 fan Units with Thermostatic control Unit	LN-FAN-THM-4FFS-CC	LN-FAN-THM-4FFS-CC	LN-FAN-THM-4FFS-CC	LN-FAN-THM-4FFS-CC	LN-FAN-THM-4FFS-CC
Horizontal Cable Management Panel 19" 1U 5 rings	LN-KDG-YKD-1UKN-CC	LN-KDG-YKD-1UKN-CC	LN-KDG-YKD-1UKN-CC	LN-KDG-YKD-1UKN-CC	LN-KDG-YKD-1UKN-CC

\*\*CC is color code: please insert BL for Black and LG for Light Grey on the part numbers while creating order

# 19" DYNAMIC Basic Free Standing and DYNAMIC Basic Server Cabinets Frequent Used Accessory Selection Chart



Frequent Used Accessories DYNAMIC Basic Series Free Standing Cabinets Sizes w:width mm d:depth mm

	w:600xd:600	w:600xd:800	w:600xd:1000	w:800xd:800	w:800xd:1000
Vertical Cable Manager	-	-	-	LN-KDG-ORG-xxEU-CC	LN-KDG-ORG-xxEU-CC

\*\* CC= Color Code, LG Light Grey RAL 7035, BL Black RAL 9005, customers to define while ordering.

\*\*\*XX is the U height of Vertical cable manager, according to selected height of cabinet, please define U height while creating order.



Frequent Used Accessories DYNAMIC Basic Series Free Standing Cabinets Sizes w:width mm d:depth mm

	w:600xd:600	w:600xd:800	w:600xd:1000	w:800xd:800	w:800xd:1000
Caster Group 2 w/breakes 2 wo/breakes	LN-ZMN-TKR-5525-XX	LN-ZMN-TKR-5525-XX	LN-ZMN-TKR-5525-XX	LN-ZMN-TKR-5525-XX	LN-ZMN-TKR-5525-XX



Frequent Used Accessories DYNAMIC Basic Series Free Standing Cabinets Sizes w:width mm d:depth mm

	w:600xd:600	w:600xd:800	w:600xd:1000	w:800xd:800	w:800xd:1000
PDU 6 way BS1363 UK type with on/off switch	LN-PRZ-ONF-1U6P-UK	LN-PRZ-ONF-1U6P-UK	LN-PRZ-ONF-1U6P-UK	LN-PRZ-ONF-1U6P-UK	LN-PRZ-ONF-1U6P-UK



Frequent Used Accessories DYNAMIC Basic Series Free Standing Cabinets Sizes w:width mm d:depth mm

	w:600xd:600	w:600xd:800	w:600xd:1000	w:800xd:800	w:800xd:1000
Mounting Hardware, Fixing M6 Cage nut set of 20	LN-DGR-KFS-M620-XX	LN-DGR-KFS-M620-XX	LN-DGR-KFS-M620-XX	LN-DGR-KFS-M620-XX	LN-DGR-KFS-M620-XX